


SelectField

SelectField (select)

This field allows you to display a list.



```
{
  "size": "s12 m12",
  "type": "select",
  "id": "api_Finder",
  "label": "API Finder",
  "validate": [
    "required"
  ],
  "icon": "find_in_page",
  "allow_add": false,
  "search": true,
  "search_error": "Brak pracowników pasujących do podanych kryteriów..",
  "placeholder": "api finder placeholder",
  "alphabetical_sorting": true,
  "define_output_value": "label",
  "add_session_id_to_api": true,
  "api_dynamic": {
    "delay": 250,
    "api": "https://kprm.int.intalio.pl/otrs/get-all-users.pl",
    "searching_label": "Trwa wyszukiwanie pracowników.."
  },
  "options": [
    {
      "value": "",
      "label": "",
      "selected": "true",
      "disabled": "disabled"
    }
  ]
},
```

allow_add

Enabling this parameter will add new things to the list. If your list is not closed, you can let new things be added to it.

Phone number

+48 123 321 123

First name

Last name

Car *

Nissan Note

Registration number *

PO 123321

ADD NEXT CAR

I have a problem with *

Choose what you have a problem with

Car

Computer

Other

Smartphone

search

It allows you to search in the list, if it is enabled together with "allow_add" you will be able to search, or if you do not find an interesting option - add your own.

search_error

If the item you are looking for is not found, the message given here will be displayed.

alphabetical_sorting

Enable alphabetical sorting of fields. If this option is disabled, the fields are displayed in the order given in the "options" parameter.

define_output_value

Each field is described by two parameters "label" and "value". If you want to, you can define here whether you want the system to be "label" or "value".

options

All available selection options.

Remember, if you don't want the first option to be checked by default, you must add an empty first option!

value

Field value.

label

Field label.

checked

Should the field be selected by default.

disabled

Is the field to be inactive by default.

api_dynamic

Added in version **1.0.24**

API Finder *

api finder placeholder

Brak danych!

This field allows you to search the api dynamically.

This field supports all other api attributes (e.g. add_session_id_to_api)

Response:

```
{
  "options": [
    {
      "value": "p. majewski",
      "label": "Piotr Majewski (p. majewski)"
    },
    {
      "value": "piotr",
      "label": "Piotr Nowak (piotr)"
    }
  ]
}
```

delay

The number of milliseconds to wait for the user to stop typing before issuing the ajax request.

api

The url that the request should be made to.

searching_label

Translation for the search text.

The rest of the available parameters:

This field supports all parameters with ["Attributes available for each field"](#).

Revision #16

Created Tue, May 26, 2020 10:56 AM by [editor](#)

Updated Wed, May 5, 2021 7:39 AM by [editor](#)