


# SelectField

## SelectField (select)

This field allows you to display a list.



```

{
  "size": "s12 m12",
  "type": "select",
  "id": "api_Finder",
  "label": "API Finder",
  "validate": [
    "required"
  ],
  "icon": "find_in_page",
  "allow_add": false,
  "search": true,
  "search_error": "Brak pracowników pasujących do podanych kryteriów..",
  "placeholder": "api finder placeholder",
  "alphabetical_sorting": true,
  "define_output_value": "label",
  "add_session_id_to_api": true,
  "api_dynamic": {
    "delay": 250,
    "api": "https://kprm.int.intalio.pl/otrs/get-all-users.pl",
    "searching_label": "Trwa wyszukiwanie pracowników.."
  },
  "options": [
    {
      "value": "",
      "label": "",
      "selected": "true",
      "disabled": "disabled"
    }
  ]
},

```

## allow\_add

Enabling this parameter will add new things to the list. If your list is not closed, you can let new things be added to it.

Phone number

+48 123 321 123

First name

Last name

Car \*

Nissan Note

Registration number \*

PO 123321

ADD NEXT CAR

I have a problem with \*

Choose what you have a problem with

Car

Computer

Other

Smartphone

## search

It allows you to search in the list, if it is enabled together with "allow\_add" you will be able to search, or if you do not find an interesting option - add your own.

## search\_error

If the item you are looking for is not found, the message given here will be displayed.

## alphabetical\_sorting

Enable alphabetical sorting of fields. If this option is disabled, the fields are displayed in the order given in the "options" parameter.

## define\_output\_value

Each field is described by two parameters "label" and "value". If you want to, you can define here whether you want the system to be "label" or "value".

# options

All available selection options.

Remember, if you don't want the first option to be checked by default, you must add an empty first option!

## value

Field value.

## label

Field label.

## checked

Should the field be selected by default.

## disabled

Is the field to be inactive by default.

## api\_dynamic

Added in version **1.0.24**

API Finder \*

api finder placeholder

Brak danych!

This field allows you to search the api dynamically.

This field supports all other api attributes (e.g. add\_session\_id\_to\_api)

### Response:

```
{
  "options": [
    {
      "value": "p. majewski",
      "label": "Piotr Majewski (p. majewski)"
    },
    {
      "value": "piotr",
      "label": "Piotr Nowak (piotr)"
    }
  ]
}
```

## delay

The number of milliseconds to wait for the user to stop typing before issuing the ajax request.

## api

The url that the request should be made to.

## searching\_label

Translation for the search text.

## The rest of the available parameters:

This field supports all parameters with ["Attributes available for each field"](#).

---

Revision #16

Created Tue, May 26, 2020 10:56 AM by [editor](#)

Updated Wed, May 5, 2021 7:39 AM by [editor](#)